


Fire Rated SafeCore® – Neutral Pressure



• Fire Rated 45 / 60 / 90 Minute



Fire Safe Products

STREK•O

A great name in doors since 1940

Product Features

Construction:	Bonded 5 Ply Hot Press
Core:	Asbestos-Free Incombustible Mineral (Blocking Available)
Door Thickness:	45 / 60 / 90 Minute 1 3/4"
Maximum Size:	Single 4/0 x 8/0 Standard Pair 8/0 x 8/0 (Require special construction)
Stiles: (Wider Stiles Available)	Neutral pressure stiles with maximum 15/32" matching hardwood edge Single: 2-3/16" Pairs: Meeting Edge: 5-1/2" Hinge Edges: 2-3/16"
Top & Bottom Rails: (Wider Rails Available)	Maximum 1/4" wood allowed on top rail and bottom rail (1/2" maximum wood allowed on bottom rail of SFD-45) Single: Top: 2-5/8" Bottom: 2-3/8" Pair: Top: 2-5/8" Bottom: 2-3/8"
Faces:	All Veneer Species, Medium Density Overlay (MDO)
Veneer Matching:	Available in Pairs, Sets & Transoms (special matching available)
Crossbands:	High Density Fiberboard (HDF)
Adhesives:	Type 1 (Waterproof)
Max Lite Openings:	<u>Metal Vision Frames:</u> (Requires approved glass)
<i>SFD-45:</i>	Total area of openings not to exceed 1296 sq. in. of visible glass or one continuous dimension of 36" in width or 54" in height
<i>SFD-90, SFD-60:</i>	Total area of openings not to exceed 100 sq. in. of visible glass or one continuous dimension of 10" in width or 33" in height
Machining/Finishing:	Prefit, Bevel & complete Factory Machining and Factory UV Finishing available
Warranty:	Life of Original Installation - <i>Warranty does not apply for exterior applications</i>
Labeling Approvals:	Intertek Testing Services/Warnock Hersey
Specifications:	Meets WDMA & AWI Quality Standards (Contact sales for label approvals)
Environmental/LEED Options:	MR4-Recycled Content/MR6-Rapidly Renewable Materials/MR7-Certified Wood/IEQ4.4-Low-Emitting Materials (No added Urea Formaldehyde Resins)